FRITZ

FCP-102

Floor Sealer

FCP-102 Floor Sealer is the best way to prepare for long lasting protection against harsh cleaners, hard wear, abrasion and strippers.

LIMITATIONS: FCP-102 is not for finished coats. It is only to be used as a base coat sealer. FCP-102 must be coated with FCP-300. Do not leave FCP-102 exposed to traffic.

MIXING & APPLICATION: No mixing required. The floor surface must be completely dry and clean before FCP-102 can be applied. Use a rayon string mop, professional bar applicator or machine. With smooth, even strokes, spread 2 coats of FCP-102 over the entire floor surface. Make sure to cover the ends of the floor all the way to the wall. Apply the first coat of FCP-102 in a vertical (north/south) direction. Allow the first coat to dry completely. Drying time for the first coat should take about 45 minutes to 1 1/2 hours. Apply the second coat following the above directions, but in a horizontal (east/west) direction, perpendicular to the first coat. This direction change allows FCP-102 to properly deposit at the tile junctures. Allow the floor to completely dry before traffic or additional top coats can be applied. Water resistance is achieved if, 24 hours after application, polish does not show any adverse effects, such as whitening, spotting or streaking when water is applied to the film for one hour.

COVERAGE: Coverage rate is approximately 1000-1250 s. ft. (153 sq. m) per 1 U.S. gallon (3.8 liters).

SHELF LIFE & WARRANTY: Storage stability: one year minimum with no jelling or separation on standing. The warranty available on this product is made in lieu of all other warranties, express or implied. Any goods proven defective within one year of manufacture will be replaced. Manufacturer will not be responsible for damages in excess of the purchase price. User shall determine suitability of the product for chosen application and user assumes all risks for its use or handling.

SAFETY PRECAUTIONS: FCP-102 is water based and non-flammable.

NOTES:

For further information, please contact: Fritz Industries, Inc. • 500 Sam Houston Rd. • Mesquite, TX 75149
Toll Free: 1-800-955-1323 • Office: (972) 285-5471 • Fax (972) 270-0179
email: tilesales@fritzind.com • www.fritztile.com

EU050803