

MATERIAL SAFETY DATA SHEET

FRITZ INDUSTRIES INC.

500 SAM HOUSTON ROAD

MESQUITE, TEXAS 75149

INFORMATION (214) 285-5471

EMERGENCY (214) 288-5425

FAX NUMBER (214) 216-3802

Product Name: FCP-300 Durogloss Date Written: October 13, 2004

Chemical Name: Acrylic Floor Polish Revision Date: October 13, 2004

Package Quantity: 1 Gal. CAS Number: N/A

Chemical Used: Acrylic Mixture Application: N/A

HMIS Rating: Health 0 Flammability 0 Reactivity 0 Special B

HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Table with columns: Hazardous Components, CAS Number, OSHA PEL, ACGIN TLV, Recommended, % (optional). Rows include Diethylene Glycol Monoethyl Ether, Tributoxo Ethyl Phosphate, Water, and Acrylic Polymers.

FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): NE Flammable Limits: NE
Explosive Limits (Lower/Upper): NA Extinguishing Media: Water, foam, dry chemical CO2
Special Fire Fighting Procedures: None
Unusual Fire and Explosion Hazards: None foreseen

PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance and Odor: Milky white liquid, mild acrylic odor.
Specific Gravity (H2O=1): 1.023 Boiling Point: 210°F
Vapor Pressure (MMHG): NE Melting Point: NA
Vapor Density: >1 Bulk Density: 8.522 lbs/gallon
Solubility In Water: Infinite pH: 8.0
Percent Volatility: 80% Biodegradability: yes
Evaporation Rate: Slower than water Freeze Point: 30°F
Pour Point: 32°F Partition COEF: NE

REACTIVITY DATA

Stability: Unstable: Stable: X Conditions To Avoid: None
Incompatibility (Materials To Avoid): None
Hazardous Polymerization: May Occur: Will Not Occur: X Conditions To Avoid: None
Hazardous Decomposition Products: Combustion may release smoke, soot, carbon dioxide, carbon monoxide.

HEALTH HAZARD DATA

Route(s) of Entry: Inhalation: Ingestion: Skin: Eyes:

Signs and Symptoms of Exposure - None expected

Inhalation:

Ingestion:

Skin:

Eyes:

Health Hazards (Acute and Chronic): None foreseen

Carcinogenic Determination NTP - No IARC Monographs - No OSHA Regulated - No

Medical Conditions Generally Aggravated by Exposure: None

Emergency and First Aid Procedures: Rinse eyes and skin contact with water.

PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled: Pick up with mop, wet vac or hose with water.

Waste Disposal Procedure: Absorb with inert material. Dispose of when dry.

Storage And Handling Conditions: Keep away from excessive heat/direct sunlight.

Precautionary Labeling: Keep from freezing

Container Disposition: Triple rinse and recycle plastic containers.

Other Precautions: None

CONTROL MEASURES

Respiratory Protection: None

Eye Protection: Splash goggles when filling/transferring liquid.

Hand Protection: None

Ventilation: None

Other Protective Equipment:

ENVIRONMENTAL EVALUATION

EPA Superfund (SARA) Title III - Hazard Classification & Associated Information: Diethylene Glycol, Monoethyl Ether.

EPA Cercla/Superfund, 40 CFR 302 (Reportable Spill Quantity): Diethylene Glycol, Monoethyl Ether.

EPA Sara Title III, CFR 355 (Extremely Hazardous Substances): No

EPA Sara Title III, 40 CFR 372 (List of Toxic Chemicals): Diethylene Glycol, Monoethyl Ether.

Components Listed On Following Chemical Inventories

TSCA X CEPA EEC ACOIN NPR DRSM

EPA -- RCRA (Hazardous Waste), 40 CRF 261: No

California Proposition 65: No

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Fritz Industries, Inc. assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.

VOC'S: 231.5 gms/liter (1.93 lbs/gal)