



---

## FCP102 FLOOR SEALER TECHNICAL INFORMATION

### General Information

FCP102 Floor Sealer is the best way to prepare a resilient flooring surface for long lasting protection against harsh cleaners, hard wear, abrasion and strippers.

### Limitations

FCP102 must be coated with FCP300. Do not leave FCP102 exposed to traffic.

### Mixing and Application

No mixing required. The floor surface must be completely dry and clean before FCP102 can be applied. Use non-linting string mop, professional bar applicator or machine. With smooth, even strokes, spread 2 coats of FCP102 over the entire floor surface. Make sure to cover the ends of the floor all the way to the wall. Apply the first coat of FCP102 in a vertical (north/south) direction. Allow the first coat to dry completely. Drying time for the first coat should take about 45 minutes to 1.5 hours. Apply the second coat following the above directions, but in a horizontal (east/west) direction, perpendicular to the first coat. This direction change allows FCP102 to properly deposit at the tile junctures. Allow the floor to completely dry before traffic and additional top coats can be applied. Water resistance is achieved if, 24 hours after application, polish does not show any adverse effects, such as whitening, spotting or streaking when water is applied to the floor for one hour.

### Coverage

Coverage Rate is approximately 1000-1250 sq ft (153 sq m) per 1 US gallon (3.8 liters).

### Shelf Life/Storage Stability

One year minimum with no jelling or separation on standing if stored in a tightly sealed container.

### Warranty

The warranty available on this product is made in lieu of all other warranties, expressed or implied. Any goods proven defective within one year of manufacture will be replaced. Manufacturer will not be responsible for damages in excess of the purchase price. User shall determine suitability of the product for chosen application and user assumes all risks for its use or handling. See warranty document for complete details.

### Safety Precautions

Eye irritant. Avoid skin and eye contact. Eye Contact: flush with water immediately for 15 minutes. Alert Medical Personnel. Skin Contact: Wash with soap and water while still wet. Ingestion: Induce vomiting, Alert Medical Personnel. In case of inhalation - move person to fresh air. Call physician if respiratory distress is not relieved by fresh air ingestion. When mixing, use adequate room ventilation to provide a positive airflow. This product is not photo-chemically reactive as defined by California Rule 102. This product is non-toxic as defined by The Federal Hazardous Substance Act, 16 CFR 1500.3. Follow all cautionary statements on product packaging.

For more information visit [www.fritztile.com](http://www.fritztile.com) or call 800-345-6202.