



FCP300 DURO-GLOSS FLOOR SEALER TECHNICAL INFORMATION

General Information

FCP300 Duro-Gloss Floor Sealer & Finish is a durable floor sealer/finish effective in renewing a glossy shine in areas that have been dulled by heavy traffic and repeated cleaning.

Limitations

FCP300 is a water-based product and should not be used on outdoor surfaces.

Mixing and Application

No mixing required. Apply directly from container. Apply FCP300 as necessary to maintain gloss appearance and rejuvenate worn traffic areas. The floor surface must be completely dry and clean. Using a non-linting string mop, professional bar applicator or machine, apply FCP300 in a thin, smooth and even strokes in a north/south direction. Allow to dry and apply a second coat in an east/west direction. Additional coats should be added as necessary to build desired performance level. Up to eight coats of FCP300 can be applied and high speed burnished for increased shine or leave unbuffered for a more subtle gloss.

Coverage

Coverage Rate is approximately 1500-2000 sq ft (185sq m) per 1 US gallon (3.8 liters)

Shelf Life/Storage Stability

One-year minimum with no jelling or separation on standing if stored in a tightly sealer container

Warranty

The warranty available on this product is made in lieu of all other warranties, expressed or implied. Any goods proven defective within one year of manufacture will be replaced. Manufacturer will not be responsible for damages in excess of the purchase price. User shall determine suitability of the product for chosen application and used assumes all risks for its use or handling. See warranty document for complete details.

Safety Precautions

Eye irritant. Avoid skin and eye contact. Eye Contact: flush with water immediately for 15 minutes. Alert Medical Personnel. Skin Contact: Wash with soap and water while still wet. Ingestion: Induce vomiting, Alert Medical Personnel. In case of inhalation - move person to fresh air. Call physician if respiratory distress is not relieved by fresh air ingestion. When mixing, use adequate room ventilation to provide a positive airflow. This product is not photo-chemically reactive as defined by California Rule 102. This product is non-toxic as defined by The Federal Hazardous Substance Act, 16 CFR 1500.3. Follow all cautionary statements on product packaging.

For more information visit www.fritztile.com or call 800-345-6202.